





Contactors 100-C / 100-CR

Contactors with 3 Main Contacts

Rated Operational Current (I_e) [A]		Ratings for Switching AC Motors – AC-2, AC-3, AC-4	Auxiliary Contacts		Cat. No.
AC-3	AC-1	3Ø kW (50 Hz)			
AC-3	AC-1	400V/415V	N.O.	N.C.	
Screw Terminals					
9	32	4	1	0	* 100-C09⊗10
			0	1	* 100-C09⊗01
12	32	5.5	1	0	* 100-C12⊗10
			0	1	* 100-C12⊗01
16	32	7.5	1	0	* 100-C16⊗10
			0	1	* 100-C16⊗01
23	32	11	1	0	* 100-C23⊗10
			0	1	* 100-C23⊗01
30	65	15	0	0	* 100-C30⊗00
37	65	18.5/20	0	0	* 100-C37⊗00
43	85	22	0	0	100-C43⊗00
55	85	30	0	0	100-C55⊗00
60	100	32	0	0	100-C60⊗00
72	100	40	0	0	100-C72⊗00
85	100	45	0	0	100-C85⊗00
97	130	55	0	0	100-C97⊗00
Spring Clamp Terminals					
9	25	4	1	0	* 100-CR09⊗10
			0	1	* 100-CR09⊗01
12	25	5.5	1	0	* 100-CR12⊗10
			0	1	* 100-CR12⊗01
16	25	7.5	1	0	* 100-CR16⊗10
			0	1	* 100-CR16⊗01

* May be ordered in package quantities of 20. Add letter **M** to the end of the cat. no. Example: **100-C09KF10M**).