

SIMATIC DP, ET 200M INTERFACE IM 153-4 PN IO FOR MAX. 12 S7-300 MODULES, EXTENDED FUNCTIONS: ISOCHRONEOUS REALTIME COMMUNICATION CLASS 1 AND 2, MODULE EXCHANGE W/O PG, OPERATION W/O MMC, MAINTENANCE NEW IO MODULES ARE SUPPORTED



Figure similar

General information	
Product type designation	IM 153-4 PN ST
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0302H
Supply voltage	
Rated value (DC)	24 V
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	In a construction with grounded reference potential, a fuse is necessary for redundant interface modules (Recommendation: 2.5 A)
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	600 mA; with 24 V DC supply
Inrush current, typ.	4 A

I ² t	0.09 A ² ·s
Output voltage	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1.5 A
Power loss	
Power loss, typ.	6 W
Address area	
Addressing volume	
• Inputs	192 byte
• Outputs	192 byte
Hardware configuration	
Number of modules per DP slave interface, max.	12
Protocols	
Bus protocol/transmission protocol	PROFINET IO
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• for module diagnostics	Yes
• Connection to network LINK (green)	Yes
• Transmit/receive RX/TX (yellow)	Yes
Potential separation	
Potential separation exists	Yes
Isolation	
Isolation tested with	500 V DC
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Air pressure acc. to IEC 60068-2-13	
• Installation altitude above sea level, max.	2 000 m
Dimensions	
Width	40 mm
Height	125 mm
Depth	118 mm
Weights	

Weight

215 g

last modified:

11/21/2017