

DPX™-IS 630 isolating switches

400 to 630 A



0 266 62



0 266 70



0 262 50

Dimensions **see e-catalogue**
Electrical characteristics **p. 170**

Isolating switches for on-load circuit breaking by visible isolation and positive action of the contacts
Padlock integrated in the handle
Supplied with terminal shields, and cage terminals
Conform to IEC 60947-3
Category of use AC 23 A
Accept electrical auxiliaries (p. 169)
Can be mounted on plate in XL³ enclosures

Pack	Cat.Nos		
			DPX-IS with release
			Can be associated with a residual current relay with separate coil (p. 155), supplied without shunt trip
	3P	4P	Front handle
1	0 266 72	0 266 74	400 A
1	0 266 73	0 266 75	630 A
			Right-hand side handle
1	0 266 76	0 266 78	400 A
1	0 266 77	0 266 79	630 A
			Left-hand side handle
1	0 266 80	0 266 82	400 A
1	0 266 81	0 266 83	630 A
			DPX-IS without release
	3P	4P	Front handle
1	0 266 60	0 266 62	400 A
1	0 266 61	0 266 63	630 A
			Right-hand side handle
1	0 266 64	0 266 66	400 A
1	0 266 65	0 266 67	630 A
			Left-hand side handle
1	0 266 68	0 266 70	400 A
1	0 266 69	0 266 71	630 A
			Rotary handles
			Direct for emergency use
			For mounting instead of standard handle
1	0 266 89		Front and right-hand side handle
1	0 266 90		Left-hand side handle
			Vari-depth handle IP 55
			Comprising: connecting rod, bracket, self-adhesive drilling template, fixing accessories (seal to maintain the IP protection up to IP 55, door lock mechanism)
1	0 266 86		For front and side handle device
1	0 266 87		For front and side handle device for emergency use
			To be ordered with Cat.Nos 0 266 89 or 0 266 90

Pack	Cat.Nos		
			Accessories
			Cage terminals
1	0 262 50		Set of 4 terminals for cable 300 mm ² max. (rigid) or 240 mm ² max. (flexible)
1	0 262 51		Set of 4 high-capacity terminals for cable 2 x 240 mm ² (rigid) or 2 x 185 mm ² (flexible)
	3P	4P	Spreaders
1	0 262 48	0 262 49	Set of incoming or outgoing spreaders
			Rear terminals
			Used to convert the fixed version with front terminals to the fixed version with rear terminals
1	0 263 52	0 263 53	Set of incoming and outgoing flat rear terminals
			Sealable terminal shields
1	0 262 45		Set of 2
			Padlock
1	0 266 97		For locking mechanism in open position Padlock with flat key N° ABA90GEL6149

