

Mosaic™ Programme surface-mounting boxes and adaptors









0 802 80 0 802 85

0 802 78



| Selection chart for boxes, supports and plates p. 900-901 | | | | |
|--|----------------------|---|--|--|
| Pack | Cat.Nos | Surface-mounting boxes | | |
| 5 5 | 0 802 80 0 802 81 | For 2 modules (support Cat.No 0 802 51) Equipped with a 20 x 12.5 mm removable entry Depth 30 mm Depth 40 mm | | |
| 2 | 0 802 89 | For 3 modules (support Cat.No 0 802 59) Equipped with a 20 x 12.5 mm removable entry Depth 40 mm | | |
| 5 | 0 802 85 | For 4, 5 or 2 x 2 horizontal modules (support Cat.No 0 802 52) Equipped with a 32 x 12.5 mm removable entry Depth 40 mm | | |
| 5 | 0 802 86 | For 6, 8 or 3 x 2 horizontal modules (support Cat.No 0 802 53) Equipped with a 32 x 12.5 mm removable entry Depth 40 mm | | |
| 2 | 0 802 84 | For 10 or 4 x 2 horizontal modules (support Cat.No 0 802 54) Equipped with a 40 x 20 mm removable entry Depth 40 mm | | |
| 5 | 0 802 82 | For 5 or 2 x 2 vertical modules (support Cat.No 0 802 52) Equipped with a 20 x 12.5 mm removable entry Depth 40 mm | | |
| 5 | 0 802 83 | For 3 x 2 vertical modules (support Cat.No 0 802 53) Equipped with a 20 x 12.5 mm removable entry Depth 40 mm | | |
| 1 | 0 802 74 | For 2 x 5, 2 x 2 x 2 modules (support Cat.No 0 802 64) or lighting environment controller Equipped with a 40 x 20 mm removable entry Depth 46 mm | | |
| 1 | 0 802 76 | For 2 x 6, 2 x 8 or 2 x 3 x 2 modules (support Cat.No 0 802 66) Equipped with a 40 x 20 mm removable entry Depth 46 mm | | |

For 2 x 10 modules (support Cat.No 0 802 68)

Equipped with a 40 x 20 mm removable entry

Depth 46 mm

| Pack | Cat.Nos | Plexo 55 modular support frames |
|------|----------------------|---|
| 10 | 0 695 80 | For 2-module Mosaic mechanisms Can be equipped with any Mosaic function in order to obtain an IP 55 wiring accessory Adaptor with smoked polycarbonate flap |
| 1 | 0 695 79 | Adaptor with smoked polycarbonate flap lockable with special tool below (not supplied) |
| 1 | 0 919 45 | Security tool |
| 1 1 | 6 806 32 6 806 33 | For 3-module Mosaic mechanisms Weatherproof IP 55 plate frames with membrane Allow operations of switches without opening cover maintaining IP 55 rating White Grey |
| | | Adaptors for mounting on Mosaic 50 mm supports |
| | | For replacing Mosaic mechanisms (50 x 50 mm) without having to change the plate or the support |
| | | frame Enable a Mosaic mechanism to be mounted on Mosaic (50 x 50 mm) screw mounting support frames |
| 10 | 0 791 54 | Adaptor for 1-module mechanism (width 22.5 x 45 mm) |
| 10 | 0 791 53 | Adaptor for 2-module mechanisms (width 45 x 45 mm) |
| | | |



Mosaic™ Programme plates, p. 904-905

