

Nylbloc™ auto

screwless connection terminals



Pack	Cat.Nos	Screwless connection terminals - Nylbloc auto
100	0 343 22	No tool direct connection after simple stripping of copper conductors Test socket for tester screwdriver for IP 2X test or Ø4 mm tip on Nylbloc auto terminals Conform to EN 60998-2-2 For rigid cable from 0.75 to 2.5 mm ² Stripping length: 11 mm Connection by separate crimping blades Transparent base providing full visibility of the connections Colour code to identify products Duplix marking possible on 3, 5 and 8-wire terminals Max. intensity: 24 A Insulating voltage: 450 V~ Grey terminal for 2 wires
100	0 343 23	Orange terminal for 3 wires
100	0 343 25	Blue terminal for 5 wires
50	0 343 28	Grey terminal for 8 wires

Pack	Cat.Nos	Accessories
5	0 343 99	Conductor stripping tool For cable desheathing and rapid wire stripping in flush-mounting and junction boxes, in trunking For cable Ø8 mm to 13 mm (from 2 G 1.5 to 5 G 2.5 mm ²) and wires 1.5 mm ² and 2.5 mm ²
10	0 343 98	Nylbloc auto terminal support For up to 3 screwless connection terminals Nylbloc auto (Cat.Nos 0 343 22/23/25/28) Direct fixing: - in top of Plexo boxes and industrial plastic cabinets ≥ 130 x 130 mm - on flat bar 12 x 2 mm - in bottom of fully assembled, adaptable and aluminium DLP trunkings (from 50 x 80 mm) Screw fixing: - in bottom of Plexo boxes ≥ 105 x 105 mm and industrial plastic cabinets - universal Fixing on rail with accessory Cat.No 0 048 11 (p. 298) Accessible test socket Marking zone with felt tip pen Cat.No 0 395 98 (p. 451)

Nylbloc™

connection strips and connectors without screws



Pack	Cat.Nos	Nylbloc connection strips																		
		12 elements with captive screws Supplied with screws undone Flame retardant polypropylene (-25 °C to +100 °C) Ambient temperature from -25 °C to +55 °C (T 55) Conform to EN 60998-2-1 and EN 60664-1 Self-extinguishing to EN 60695-2-11 at 850° Insulation voltage: 250 V according to EN 60 998-2-1 Use at 400 V integrated in a series of products that comply with the requirements of EN 60664-1, pollution degree 2, overload category III																		
		<table border="1"> <thead> <tr> <th>Rated capacity (mm²)</th> <th>Hole Ø (mm)</th> <th>Max current (A)</th> </tr> </thead> <tbody> <tr> <td>2.5</td> <td>2.5</td> <td>24</td> </tr> <tr> <td>6</td> <td>3.5</td> <td>41</td> </tr> <tr> <td>10</td> <td>4.5</td> <td>57</td> </tr> <tr> <td>16</td> <td>5.5</td> <td>76</td> </tr> <tr> <td>25</td> <td>7</td> <td>101</td> </tr> </tbody> </table>	Rated capacity (mm ²)	Hole Ø (mm)	Max current (A)	2.5	2.5	24	6	3.5	41	10	4.5	57	16	5.5	76	25	7	101
Rated capacity (mm ²)	Hole Ø (mm)	Max current (A)																		
2.5	2.5	24																		
6	3.5	41																		
10	4.5	57																		
16	5.5	76																		
25	7	101																		
10	0 342 11	Black																		
10	0 342 13	Black																		
10	0 342 15	Black																		
10	0 342 17	Black																		
10	0 342 19	Black																		
10	0 342 21	White																		
10	0 342 23	White																		
10	0 342 25	White																		
10	0 342 27	White																		

Pack	Cat.Nos	Connectors without screws - Capvis caps																												
		Rapid connection for 1.5 - 2.5 - 4 and 6 mm ² solid conductor cables - 440 V insulation																												
		<table border="1"> <thead> <tr> <th>Nominal capacity (mm²)</th> <th>No of cables and corresponding sections (mm²)</th> <th>Cap colour</th> <th>Packaging type</th> </tr> </thead> <tbody> <tr> <td>1.5</td> <td>3 to 5 of 0.5² 2 to 4 of 0.75²</td> <td>blue</td> <td>box</td> </tr> <tr> <td>1.5 to 2.5</td> <td>2 of 1.5² 3 to 5 of 0.5² 2 to 5 of 0.75² 2 to 3 of 1.5²</td> <td>orange</td> <td>box</td> </tr> <tr> <td>4</td> <td>2 of 2.5² 2 to 4 of 1.5² 2 to 3 of 2.5²</td> <td>yellow</td> <td>box</td> </tr> <tr> <td>6</td> <td>2 of 4² 2 to 5 of 2.5² 2 to 3 of 4²</td> <td>red</td> <td>box</td> </tr> <tr> <td>2 000</td> <td>2 of 6² 2 to 4 of 1.5² 2 to 3 of 2.5²</td> <td>yellow</td> <td>bucket</td> </tr> <tr> <td>1 500</td> <td>2 of 4² 2 to 5 of 2.5² 2 to 3 of 4² 2 of 6²</td> <td>red</td> <td>bucket</td> </tr> </tbody> </table>	Nominal capacity (mm ²)	No of cables and corresponding sections (mm ²)	Cap colour	Packaging type	1.5	3 to 5 of 0.5 ² 2 to 4 of 0.75 ²	blue	box	1.5 to 2.5	2 of 1.5 ² 3 to 5 of 0.5 ² 2 to 5 of 0.75 ² 2 to 3 of 1.5 ²	orange	box	4	2 of 2.5 ² 2 to 4 of 1.5 ² 2 to 3 of 2.5 ²	yellow	box	6	2 of 4 ² 2 to 5 of 2.5 ² 2 to 3 of 4 ²	red	box	2 000	2 of 6 ² 2 to 4 of 1.5 ² 2 to 3 of 2.5 ²	yellow	bucket	1 500	2 of 4 ² 2 to 5 of 2.5 ² 2 to 3 of 4 ² 2 of 6 ²	red	bucket
Nominal capacity (mm ²)	No of cables and corresponding sections (mm ²)	Cap colour	Packaging type																											
1.5	3 to 5 of 0.5 ² 2 to 4 of 0.75 ²	blue	box																											
1.5 to 2.5	2 of 1.5 ² 3 to 5 of 0.5 ² 2 to 5 of 0.75 ² 2 to 3 of 1.5 ²	orange	box																											
4	2 of 2.5 ² 2 to 4 of 1.5 ² 2 to 3 of 2.5 ²	yellow	box																											
6	2 of 4 ² 2 to 5 of 2.5 ² 2 to 3 of 4 ²	red	box																											
2 000	2 of 6 ² 2 to 4 of 1.5 ² 2 to 3 of 2.5 ²	yellow	bucket																											
1 500	2 of 4 ² 2 to 5 of 2.5 ² 2 to 3 of 4 ² 2 of 6 ²	red	bucket																											
1000	0 343 38	1.5																												
100	0 343 44	1.5 to 2.5																												
100	0 343 51	4																												
100	0 343 57	6																												
2 000	6 340 51	4																												
1 500	6 340 52	6																												